

INDEPENDENT TESTING SERVICES LIMITED

Testing & Inspection Services to the Civil Engineering Industry

Independent Testing Services Limited
5, Main Street
Portarlinton
Co. Laois
Registered in Ireland, No. 368795

Telephone: +353 (0)57 8642810
Fax: +353 (0)57 8642786
Mobile Tel: +353(0)87 4173203

TEST REPORT No. RN3171

**Dust Monitoring using the
Bergerhoff Method**

**Site: Primary Care Centre,
Grangegorman Upper, Dublin 7**

Monitoring Period: 6th July to 6th August 2015

I.T.S. Job No. JN2312

Prepared for: L & M Keating Ltd.

CONTENTS

- 1 INTRODUCTION
- 2 SITE DETAILS
- 3 PRINCIPLE OF THE BERGERHOFF METHOD
- 4 METHODOLOGY
- 5 RESULTS OF DUST MONITORING

APPENDIX

LABORATORY ANALYSIS CERTIFICATE

S. Dixon

Simon Dixon

Director

For and on behalf of Independent Testing Services Limited.

1 INTRODUCTION

Independent Testing Services Limited were instructed by L & M Keating Ltd to carry out dust monitoring at their site at Grangegorman Upper, Dublin 7.

The purpose of monitoring was to determine the average monthly dust deposition at two locations on the site boundary using the Bergerhoff Method.

This report presents the results of the dust monitoring for the period between 6th July and 6th August 2015.

2 SITE DETAILS

The site at Grangegorman is currently undergoing redevelopment, including the refurbishment of existing buildings and the construction of new buildings. Of particular relevance to the generation of air-borne dust is the heaping of soils into a number of piles for future use or disposal.

3 PRINCIPLE OF THE BERGERHOFF METHOD

The Bergerhoff Method is described in the standards BS1747 Part 1: *Methods for the measurement of air pollution. Deposit gauges*, and VDI 4320 Part 2 *Measurement of atmospheric depositions - Determination of the dust deposition according to the Bergerhoff method* (the latter published by the German Engineering Institute).

With reference to BS6069 Part 2, dust is characterised as encompassing solid Particulate Matter (PM) with a particle size of between 1 and 75 microns (1 - 75 µm). Dust can become suspended in the atmosphere from many sources, both natural (pollen/spores, sea salt, soil volcanic ash, fires, etc.) and anthropogenic (construction/demolition, minerals extraction, agriculture, industry, transport, leisure activities, etc.). Construction activities are likely to generate some dust emissions, depending on the dust mitigation measures adhered to on the particular site.

Dust deposition typically occurs in close proximity to the source, and potential dust impacts may occur within 500 meters of the dust generating activity as dust particles fall out of suspension in the air. Larger particles deposit closer to the generating source and deposition rates will decrease with distance from the source.

Health effects are associated with fine particles smaller than 10 µm in size (PM₁₀). “Nuisance dust” (when deposited to ground, buildings, or other materials) is generally associated with the coarse fraction particulates, greater than 20 µm in size.

The Bergerhoff Method uses dust deposition gauges to measure the total particulate matter that is deposited into a collecting vessel by its own weight, or by the assistance of rainfall.

The total amount of dust deposited in the collection vessel during the monitoring period is determined by laboratory analysis, *i.e.* the weight of the total insoluble residue on evaporation. The average monthly deposition is expressed as the weight of dust that has been collected per unit area per day.

4 METHODOLOGY

The dust deposition was sampled at 2 no. monitoring stations within the Grangegorman site, using Bergerhoff Dust Deposition Gauges which were installed at locations specified by L & M Keating Ltd.

The location references for the dust monitoring stations are as follows:

- Monitoring Station 1: Left side of gate looking out onto Grangegorman Upper.
- Monitoring Station 2: Right side of gate looking out onto Grangegorman Upper.

The period of monitoring was from 6th July 2015 to 6th August 2015, *i.e.* 31 days.

The collected samples were laboratory analysed by BHP Laboratories, using gravimetric weight analysis, to determine the amount of dust deposition.

5 RESULTS OF DUST MONITORING

The laboratory analysis certificate is included in the Appendix of this Report.

The results of the dust monitoring at the Grangegorman site can be summarised as follows:

Monitoring Station 1

Monitoring period:	6 th July 2015 to 6 th August 2015
Number of days:	31
Collecting surface area:	6.082 x 10 ⁻³ m ²
Total dust deposition:	5.6 mg
Average Dust Deposition:	29.0 mg/m²/day

Monitoring Station 2

Monitoring period:	6 th July 2015 to 6 th August 2015
Number of days:	31
Collecting surface area:	$6.082 \times 10^{-3} \text{ m}^2$
Total dust deposition:	8.1 mg
Average Dust Deposition:	42.0 mg/m²/day

APPENDIX

LABORATORY ANALYSIS CERTIFICATE

TEST REPORT NO.: 118501

Analysing
Testing
Consulting
Calibrating



Client: Independent Testing Services Ltd
5 Main Street
Portarlinton
Co. Laois

BHP Ref. No.: 15/08/166-167
Order No.:
Date Received: 07/08/15
Date Completed: 11/08/15
Test Specification: Nil
Item : See below

BHP
New Road
Thomondgate
Limerick
Ireland
Tel +353 61 455399
Fax + 353 61 455447
E Mail bhpccm2@bhp.ie

FTAO: Mr Simon Dixon

TEST	Client Reference	Units	Results	Standard Reference
Residue Dust Deposition	Monitoring Station 1 06/07/15 to 06/08/15	mg mg/m ² /day	5.6 29.0	VDI-4320 Part 2 VDI-4320 Part 2
Residue Dust Deposition	Monitoring Station 2 06/07/15 to 06/08/15	mg mg/m ² /day	8.1 42.0	VDI-4320 Part 2 VDI-4320 Part 2

Additional Information: All Sample locations are inside the EPA Limit of 350 mg/m²/day.
*Monitoring period provided by Independent Testing Services Ltd

For and on behalf of BHP laboratories :

Colette Hannan
Issue Date : 18/08/15

This Test Report shall not be duplicated except in full and then only with the permission of the test laboratory